

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://payapress.nt-rt.ru/> || pfy@nt-rt.ru

Name: Busbar Fabrication Machine
Model: HBC-BE 120/160



- Bender controller equipped by **spring back compensation** system
- Digital bending indicator leads to perfect bending result
- Rotatable plates prevent fractions in busbar surface
- **Z-shape mold** :To create too closed bends in one stroke
- **Edge bending mold** :to bend busbar from edge side
- **Twist bending mold** : to twist busbar for special purpose

MODEL	HBC-BE120	HBC-BE160
Function	Bending busbars	Bending babars
Bender capacity	Up to 120 x 12 mm	Up to 160 x 15 mm
Bender controller	Electronic controller High accuracy encoder	Electronic controller High accuracy encoder
Bender molds	Z-shape mold(optional) Edge bending mold(optional) Twist mold(optional) End-bending (mold(optional)	Z-shape mold(optional) Edge bending mold(optional) Twist mold(optional) End-(bending mold(optional)
Length measuring in bende	Handy metering system programmable metering (System(optional)	Handy metering system Programmable (metering System(optional)
Hydraulic system	power pack Double acting system 1	power pack Double acting system 1
Operating pressure	bar 250	bar 250
Power rating	x 1.5 Kw 1	x 1.5 Kw 1
Voltage	Volt-3/50 Hz 380	Volt-3/50 Hz 380
Oil	Hydraulic oil H68 – 30 liters	Hydraulic oil H68 – 30 liters
Mail desk dimension	x 110 x 100(H) cm 130	x 110 x 100(H) cm 130